

PAINT REMOVER

Industrial Paint Remover



Description:

PAINT REMOVER is solvent-based remover designed for removal of paints (acrylic, polyurethane and epoxy) from metal surfaces. Paint Remover is thixotropic, mildly alkaline chemical liquid that penetrates the paint and ensures its easy removal. Do not use Paint Remover for paint stripping over plastics, plastic tiles, linoleum or fibers. This product is ready for use.

Uses:

PAINT REMOVER can be applied to facilitate stain removal in the following cases;

- Remove any paints, graffiti, etc.
- Acrylic Varnishes.
- Residue of gasoline.
- Epoxy and polyurethane paints.
- Adhesive residues and epoxy joints created during the bonding of ceramic tiles.

Advantages:

- Non-flammable.
- Low toxicity.
- Non-VOC.
- Mildly alkaline chemical liquid that penetrates the paint and ensures its easy removal.

Company Standard Compliance:



Technical Information:

Properties	Specification
------------	---------------

Color	White
Consistency	Liquid
Chemical Substance	Aromatic
Density	1.10 ± 0.05

Method of application:

Application:

- Aromatic 1.10 ± 0.05 Before applying PAINT REMOVER, protect any surface that may be damaged when in contact solvents. Apply PAINT REMOVER as it is without dilution, evenly, with a brush. When the coating has softened (5-10 minutes) with a soft brush or cloth lightly rubbing the surface, remove residues. In difficult places, repeat the procedure if necessary. Finally rinse the surface with cold water and detergent.

Limitation:

- Do not use PAINT REMOVER for paint stripping over plastic, plastic tiles, linoleum etc.
- Do not use on synthetic surfaces such as rubber, polystyrene, vinyl flooring etc.
- Not compatible with synthetic fabrics and fiberglass.
- Do not use in good quality wood without testing.
- Do not apply at the substrate and ambient temperatures lower than +5°C and higher than +35°C.

Consumption:

Depending on the application 50-80ml/m².

Packaging:

It is supplied in 1 lit pack.

Storage & Shelf-life:

PAINT REMOVER remains stable for at least 24 months from the production date in the original sealed packaging stored in a dry place and temperature between +5°C and +35°C.




Health & Safety:

For information and instructions regarding disposal and safe handling, users should refer to the latest safety data sheet of the product containing ecological, toxicological and other safety-related data.

Legal notice:

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from these shown. For the latest and a valid version of the technical datasheet the user of the material must refer to our website www.redwop.net

	It is the practice of increasing efficiency with which buildings use resources- energy, water and materials-while reducing building impacts on human health and the environment.
	ISO 45001 is the world's international standard for occupational health and safety, issued to protect employees and visitors from work-related accidents and diseases.
	ISO 9001:2015 is a globally recognized standard for quality management systems (QMS). It helps organizations of all sizes and sectors to: Improve performance, Meet customer expectations, Demonstrate commitment to quality, and Identify and improve processes that lack consistency.
	ISO 14001 is the internationally recognized standard for environmental management systems (EMS). It provides a framework for organizations to design and implement an EMS, and continually improve their environmental performance

	This symbol is used to identify Redwop products which give off a low level of volatile organic compounds(VOC) as certified by GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.), an international organisation for controlling the level of emissions from products used for floors.
	Our Commitment To The Environment Redwop products assist Project Designers and Contractors create innovative LEED (The Leadership in Energy and Environmental Design) certified projects, in compliance with the U.S. Green Building Council.
	ISO/IEC 17025 enables laboratories to demonstrate that they operate competently and generate valid results, thereby promoting confidence in their work both nationally and around the world.

Country: India

format: RCPL/QC/025-00

issue Date: 2024-12-01 10:24:12