



Tiles De-bonded

Reason For de bonding

1. Application of adhesive on saline or moist surface.
2. Lack of gap between tiles for movement like Expansion & Contraction.
3. Not using a steel trowel on both the tile and surface leads to poor bonding.
4. Adding extra cement and sand reduces the adhesive's bonding strength.
5. Any force or shock stronger than the bond strength can cause tiles to come off.

Mitigation:

- Make sure cement plaster, RCC, AAC blocks, and red bricks are clean before applying adhesive.
- Always provide gaps between tiles, especially in outdoor or open areas, to allow for movement.
- Apply adhesive using a steel trowel on both the back of the tile and the wall/floor surface.
- Apply **ADMIX EXTRA BOND** to improve the bonding strength between the tile and the surface.

Proper Product Consultation as per tile size and condition

Sr.	Vitrified Tiles Size	Product Recommended TERATILE
1.	2"x2"	SILVER, GP, GOLD
2.	2"x4"	GOLD, MP, SINEX
3.	4"x4"	GOLD, MP, SINEX

4.	4"x6"	DIAMOND, PLATINUM
5.	6"x8"	PROLIX, PROLIX EXTRA
6.	4"x8"	PROLIX, PROLIX EXTRA
7.	10"x10" or above	PROLIX, PROLIX EXTRA

Notes: For Extra bonding strength **ADMIX EXTRA BOND** is recommended.



Country: India

format:

issue Date: 2024-12-01 10:45:36